



Certificate number: 2311787 (1)

Issued 29/11/2023 Expires 29/11/2028

# Kiwa Regulation 4 (KUKreg4) Certification

Evaluation Guideline – Kiwa UK – EG004 – Regulation 4(1)(a) Model number(s) – see Appendix

# Fluidlytix LLC.

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied upon to comply with the Kiwa Evaluation Guideline referred above.

Which verifies the requirements of:

Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales: 2009 Northern Ireland and 2014 Byelaws Scotland.

This certificate has been issued in accordance with the Kiwa regulations for product certification.

Signed on behalf of Kiwa Watertec

DAY.

David Jay, Business Unit Manager – Authorised Signatory Kiwa Watertec

Publication of this certificate is allowed.

Products are intended to be used in the UK only. For other countries, other (National) requirements will apply. See <a href="https://www.kiwa.com/gb/en/about-kiwa/water-products/">https://www.kiwa.com/gb/en/about-kiwa/water-products/</a> or the QR code below to ensure that the certificate is still valid.

#### Kiwa Watertec

(A Trading Division of Kiwa Ltd) 26A Rassau Industrial Estate

Ebbw Vale Gwent NP23 5SD

United Kingdom

**T** +44 (0)1495 308185

uk.water@kiwa.com www.kiwa.co.uk

### **Certificate Issued to:**

Fluidlytix LLC 4447 N Central Expy 110 - 108 Dallas Texas 75025 United States





# **Product Certificate**



Appendix to Certificate number: 2311787

## The following products belong to this certificate

## PRODUCT DESCRIPTION

Range of water saving valves with stainless steel bodies and EPDM 'o' rings for insertion into specifically dimensions bores. ATS3 - Without Production Surveillance.

MODEL(S)

3/4" BAA

1" 1AA

1 1/2" CAA

2" 2AA

3" 3AA/3BA

4" 4AA/4BA

6" 6AA/6BA

8" 8AA/8BA

10" 10AA/10BA

SIZE:

See model.

SCOPE:

Manufacturer recommended maximum working pressure 13.78 Bar & maximum operating temperature 85°C.

Hygienic Purposes: Non-metallic materials suitable for continuous use up to 85°C.

**MARKING** 

WAVEm flow arrow, NSF/ANSI, Made int eh USA and Model number on body.

**MATERIALS** 

Non-metallic materials assessed (BS6920) to point of discharge.

**BACKFLOW PROTECTION NOTES** 

N/A.

ADDITIONAL NOTES

All water contact & exposed components satisfy opacity requirements.

No testing has been conducted to verify its water saving characteristics or performance.

### **Extra Notes**